

TECHNICAL SPECIFICATIONS

Voltage	10-30 V		
LED colour	White		
Charge Time	<4 h		
Consumption	< 1A		
Functions	High Intensity, Low Intensity, Flashing Mode		
	HIGH INTENSITY	FLASHING MODE	LOW INTENSITY
Battery Life	>2 h	>6 h	>8 h
Lumens	700 lm	220 lm	110 lm
Flashlight dimensions	77 x 77 x 210 mm		
Charger dimensions	65 x 72 x 100 mm		
Flashlight weight	437 gr.		



L560 Series

Professional Rechargeable Flashlights



HOW TO ORDER:

Select a reference number from the list below:

2101171 L560, rechargeable flashlight

ACCESSORIES:

Charger unit

2101176REC CL560, flashlight charger 10-30V, only for L560

Light-spreader

- 9151270 DL500, light-spreader cone for L500 series flashlight, (fluorescent yellow color)
- 9151270-01 DL500, light-spreader cone for L500 series flashlight, (fluorescent red color)
- 9151270-02 DL500, light-spreader cone for L500 series flashlight, (white)
- 2101099 DL500/2C, light-spreader cone for L500 series flashlight, amber/red spreading-Lens
- 2101100 DL500/3C, light-spreader cone for L500 series flashlight, white/amber/red spreading-Lens
- 2101101 DL500/3C, light-spreader cone for L500 series flashlight, white/green/red spreading-Lens

Paddles

1005066 PD500, luminous paddle for L500 series flashlight w/'Stop' and Arrows Signs

Supports for light-spreader and paddle

- 8299018 SCO-500/400, metal bracket for flashlight cone, black
- 8136813 SPD-500/400, luminous paddle metal bracket, Series L500

Contact our Sales Department for further information.

L560 Series



Federal Signal Vama presents the compact and rechargeable flashlight L560, designed to make the security and surveillance professionals' jobs easier, providing a great luminosity and reliability in a small size and weight, making it the perfect complement to your daily work.

Has a great versatility, as the flashlight allows to adapt numerous accessories, it has an adjustable focus and 3 working modes (high intensity, low intensity and flashing mode). The flashlight L560 has a light autonomy of more than 8 hours.

COMPACT and LIGHT-WEIGHT

The L560 only measures 210 mm and weighs 437 gr.



The L560 flashlight provides 3 different functions: high intensity, low intensity and flashing mode.

Adjustable focus



COMPACT AND LIGHT-WEIGHT: Thanks to its weight of only 437 gr. and to its small dimensions, the flashlight L560 is very easy to use.

AUTONOMY: The low consumption LED of the L560 flashlight guarantees a light autonomy up to 8 hours.

3 WORKING MODES: The flashlight provides 3 different functions, to adapt it according to each need: High intensity, Low intensity and Flashing mode.

ADJUSTABLE FOCUS: The flashlight L560 allows to adjust the light beam according to the object or scene to be focused.

DROP AND WATER PROOF: It is designed with great resistant materials avoiding that the flashlight gets damaged due to falls or impacts. It is also dust and water resistant (IP55).

BETTER GRIP AND ANTI-SLIP: Its cylindrical aluminium body provides a great resistance and better grip. The flashlight head is made of wrinkled rubber, which avoids that it rolls while leaving in a plain surface.



L500 Series accessories range

ACCESSORIES

- DL500, light-spreader cone
Made in yellow, red or white plastic.
- DL500, multicoloured light-spreader cone
Made in red/amber, white/red/amber and white/red/green.
- SCO-500/400, light-spreader cone bracket
Metal bracket for vehicle storage of the cones, available in black colour, suitable for all light-spreader cone models.
- PD500, light-spreader paddle
"STOP/Arrow" sign.
- SPD-500/400, light-spreader paddle bracket
Metal bracket for vehicle storage of the luminous paddles.
- CL560, flashlight charger
CL560, flashlight charger 10-30V, only for L560.



Flashlight charger with LED charging indicator.

Dimensions in mm:

